FINAL SCOPING REPORT

Bennington Streetscape Improvement Project BENNINGTON STP SDWK (12)

August 2014



Bennington County Regional Commission





Table of Contents

Purpose & Need 3	
Project Area Photos 5	
Conceptual Plans Aldi Driveway to Performance Drive Performance Drive to East Road	6 13
Cost Estimate 17	
Appendix Bike/Pedestrian Count 21 Capacity and Delay Analysis 22	
Traffic Count 27	

PURPOSE & NEED

<u>Statement of Purpose and Need</u> Bennington Streetscape Improvement Project Bennington STP SDWK (12)

Project Purpose

The purpose of this project is to create safe and appealing pedestrian access, with accommodations for bicycles where possible, along Northside Drive / Kocher Drive near the intersection with US Route 7.

Project need

The project area has high traffic volume but no facilities for pedestrians or cyclists who must tolerate unsafe conditions to use the roadway. Kocher Drive/Northside Drive is the only east-west passage for 2.3 miles between Houghton Lane and County Street and is a key link in the local transportation network.

The route is a developed commercial "strip" with large retail stores, offices, and industrial parks. US 7 is a 6-lane wide limited-access highway immediately north of the Kocher Drive/US 7 intersection which has no pedestrian accommodations, acting as a barrier to east-west pedestrian movement, and has the highest traffic volume in the region. These roadways and intersections are a deterrent, discouraging pedestrian travel between the region's most populous residential neighborhood to the south and the commercial uses to the north and west.

Mount Anthony Union Middle School, Mount Anthony Union High School, Grace Christian School and Molly Stark Elementary School are all nearby, and many children walk along the edge of the roadway and cross the Kocher Drive/US 7 intersection. Notably, the middle school has a wide multi-use path used by many students, which extends to the eastern edge of the project area, yet does not connect west through the project area to the neighborhoods on the western side. It is likely that many other children choose not to walk to school because of the lack of safe and appealing pedestrian facilities. There is growing evidence that infrastructure that promotes driving over "active transportation" has contributed to the public health epidemics of childhood obesity and type 2 diabetes.

Many additional concerns and deficiencies with the project area's intersections and roadways support the purpose including:

- Despite the numerous pedestrians and cyclists who use the roadway, there are no sidewalks (except on Northside Drive west of Benmont Avenue), crosswalks, pedestrian signals, or bike lanes, and only limited paved roadway shoulders.
- The lack of pedestrian facilities encourages driving, even for short trips, and limits transportation options.
- All three of the project area's intersections are high crash locations (HCLs).
- The bridge on Kocher Drive is too narrow to safely accommodate pedestrians, cyclists and motor vehicles.
- Roadway hardware (guardrail, signal mast poles and drainage structures) adjacent to the roadway pushes pedestrians and cyclists close to motor vehicle traffic.
- Steep slopes at the roadway's edge limit space for pedestrians.
- The lack of street trees or landscaping makes walking less appealing and does not promote traffic calming.
- Inadequate lighting makes it difficult to see pedestrians and cyclists at night.

Project Area Photos


















CONCEPTUAL PLANS

ALDI DRIVEWAY TO PERFORMANCE DRIVE

(STATE PROJECT)


BENNINGTON COUNTY REGIONAL COMMISSION



KOCHER DRIVE STREETSCAPE IMPROVEMENTS ALDI DRIVEWAY TO PERFORMANCE DRIVE BENNINGTON STP SDWK (12)

INDEX OF SHEETS

- I TITLE SHEET
- 2 GENERAL PROJECT LAYOUT
- 3 CONCEPTUAL PLAN I
- 4 CONCEPTUAL PLAN 2
- 5 TYPICAL SECTIONS I
- 6 TYPICAL SECTIONS 2



CONVENTIONAL SYMBOLS COUNTY LINE TOWN LINE LIMITS OF ACCESS POINT OF ACCESS FENCE LINE STONE WALL TRAVELED WAY GUARD RAIL RAILROAD SURVEY LINE CUI VERT POWER POLE TELEPHONE POLE TREES CONTROL OF ACCESS PROPERTY LINE R.O.W. TAKING LINE SLOPE RIGHTS TOP OF CUT TOE OF SLOPE

DATUM VERTICAL NGVD 88 HORIZONTAL NAD 83 CONCEPTUAL PLAN - NOT FOR CONSTRUCTION

DC

URS

JRS PROJECT NO.

38397221

URS CORPORATION
3 CORPORATE DRIVE, SUITE 203
CLIFTON PARK, NY 12065
PH# (518) 688-0015

PLANS PREPARED BY:

BEHAN PLANNING
AND DESIGN

II2 SPRING STREET, SUITE 305 SARATOGA SPRINGS, NY 12866 (518) 583-4335 BCRC PROJECT MANAGER : MARK ANDERS

URS PROJECT MANAGER : MARK ARMBRUST

PROJECT NAME : KOCHER DRIVE STREETSCAPE

CANADA

MASSACHUSETTS

State of NEW HAMPSHIRE


State of NEW YORK

STATE PLANE

PROJECT NUMBER : STP SDWK (12)
SHEET 1 OF 6 SHEETS

PROJECT DESCRIPTION

- I. CONSTRUCT A 10' WIDE WALKWAY WITH BUFFER STRIP FROM EDGE OF TRAVEL LANE TO THE WALKWAY (APPROXIMATELY 10' WIDE) ALONG THE NORTH SIDE OF NORTHSIDE DRIVE AND KOCHER DRIVE FROM THE ALDI DRIVEWAY TO PERFORMANCE DRIVE.
- 2. INSTALL PEDESTRIAN SIGNALS AT THE ALDI INTERSECTION AND THE ROUTE 7 INTERSECTION.
- 3. INSTALL CROSSWALK PAVEMENT MARKINGS AT STREET AND DRIVEWAY CROSSINGS.
- 4. CONSTRUCT A CONCRETE SIDEWALK WITH CURB ACROSS THE FURNACE BROOK BRIDGE, INCLUDING INSTALLATION OF A PEDESTRIAL RAILING AND LANE SHIFT.
- 5. INSTALL DRAINAGE INLETS AND PIPING IN THE BUFFER STRIP ALONG NORTHSIDE DRIVE AND EAST OF THE





TOWN OF BENNINGTON, VERMONT



II2 SPRING STREET, SUITE 305 SARATOGA SPRINGS, NY 12866 (518) 688-0015

3 CORPORATE DRIVE, SUITE 203 CLIFTON PARK, NY 12065

PROJECT NAME: KOCHER DRIVE STREETSCAPE IMPROVEMENTS

PROJECT NUMBER: STP SDWK (12)

FILE NAME: concep_design_gpl_VTrans. @ DATE: 8/14/2014 PROJECT LEADER: M. ARMBRUST DESIGNED BY: C. BEHAN GENERAL PROJECT LAYOUT

N


PLANE

STATE

(518) 688-0015

CONCEPTUAL PLANS I

SHEET 3 OF 6








(518) 688-0015


TOWN OF BENNINGTON, VERMONT PROJECT NAME: KOCHER DRIVE STREETSCAPE IMPROVEMENTS

PROJECT NUMBER: STP SDWK (12)


FILE NAME: concep_design2_VTrans.dgnPLOT DATE: 8/14/2014 PROJECT LEADER: M. ARMBRUST DRAWN BY: M. WASSON DESIGNED BY: C. BEHAN CHECKED BY: SHEET 4 OF 6 CONCEPTUAL PLANS 2




TYPICAL SECTION | NORTHSIDE DRIVE / KOCHER DRIVE (US7 TO GRACE CHRISTIAN SCHOOL DRIVEWAY) NOT TO SCALE



TYPICAL SECTION 2 KOCHER DRIVE - BRIDGE OVER FURNACE BROOK NOT TO SCALE



DETAIL A NOT TO SCALE



TYPICAL SECTION 3 US ROUTE 7 - KOCHER DRIVE TO 305 FEET NORTH OF KOCHER DRIVE NOT TO SCALE

URS CORPORATION 3 CORPORATE DRIVE, SUITE 203 CLIFTON PARK, NY 12065 II2 SPRING STREET, SUITE 305 SARATOGA SPRINGS, NY 12866 (518) 583-4335 (518) 688-0015

BEHAN PLANNING


AND DESIGN

TOWN OF BENNINGTON, VERMONT

PROJECT NAME: KOCHER DRIVE STREETSCAPE IMPROVEMENTS

PROJECT NUMBER: STP SDWK (12)


FILE NAME: concep_design_typ_VTrans. @dynOT DATE: 8/14/2014 PROJECT LEADER: M. ARMBRUST DRAWN BY: M. WASSON DESIGNED BY: C. BEHAN CHECKED BY: SHEET 5 OF 6 TYPICAL SECTIONS I



TYPICAL SECTION 4

KOCHER DRIVE - AT APPROACHES TO BRIDGE OVER FURNACE BROOK (WITHIN EXISTING ROADWAY)

NOT TO SCALE



TYPICAL SECTION 5

KOCHER DRIVE - EAST OF FURNACE BROOK TO PERFORMANCE DRIVE

NOT TO SCALE



TOWN OF BENNINGTON, VERMONT PROJECT NAME: KOCHER DRIVE STREETSCAPE IMPROVEMENTS



CONCEPTUAL PLANS


PERFORMANCE DRIVE TO EAST ROAD

(TOWN PROJECT)

BENNINGTON COUNTY REGIONAL COMMISSION








INDEX OF SHEETS

- TITLE SHEET
- 2 CONCEPTUAL PLAN
- 3 TYPICAL SECTIONS



CONVENTIONAL SYMBOLS COUNTY LINE TOWN LINE LIMITS OF ACCESS POINT OF ACCESS FENCE LINE STONE WALL TRAVELED WAY GUARD RAIL RAILROAD SURVEY LINE CULVERT POWER POLE TELEPHONE POLE TREES CONTROL OF ACCESS PROPERTY LINE R.O.W. TAKING LINE SLOPE RIGHTS TOP OF CUT TOE OF SLOPE

VERTICAL NGVD 88 HORIZONTAL NAD 83 CONCEPTUAL PLAN - NOT FOR CONSTRUCTION

PLANS PREPARED BY:

URS URS CORPORATION

3 CORPORATE DRIVE, SUITE 203 CLIFTON PARK, NY 12065 PH# (5I8) 688-00I5

BEHAN PLANNING AND DESIGN

II2 SPRING STREET, SUITE 305 SARATOGA SPRINGS, NY 12866 (518) 583-4335

BCRC PROJECT MANAGER : MARK ANDERS

URS PROJECT MANAGER : MARK ARMBRUST

PROJECT NAME : KOCHER DRIVE STREETSCAPE IMPROVEMENTS

PROJECT NUMBER : TBD SHEET 1 OF 3 SHEETS

JRS PROJECT NO. 38397221


DESIGNED BY: C. BEHAN

KONCEPTUAL PLAN

(518) 688-0015

CHECKED BY:

SHEET 2 OF 3



TYPICAL SECTION

KOCHER DRIVE - PERFORMANCE DRIVE TO EAST ROAD

NOT TO SCALE

TOWN OF BENNINGTON, VERMONT






PROJECT NAME: KOCHER DRIVE STREETSCAPE IMPROVEMENTS

PROJECT NUMBER: TBD

FILE NAME: concep_design_typ_Town.dgmPLOT DATE: 8/14/2014
PROJECT LEADER: M. ARMBRUST DRAWN BY: M. WASSON
DESIGNED BY: C. BEHAN CHECKED BY:
TYPICAL SECTIONS SHEET 3 OF 3



Kocher Drive Streetscape Improvements Construction Estimate - State August 2014

ITEM NO.	DESCRIPTION	UNIT	VAOT 5 YR AVG PRICE	ESTIMATED QUANTITY STATE	TOTAL COST STATE
201.11	CLEARING AND GRUBBING	ACRE	\$12,400.00	0.4	\$4,960.00
203.30	EARTH BORROW	CY	\$9.82	5760	\$56,563.20
301.25	SUBBASE OF CRUSHED GRAVEL, COARSE GRADED	CY	\$33.90	320	\$10,848.00
525.44	BRIDGE RAILING	LF	\$110.00	40	\$4,400.00
601.2610	15" DIA. CPEP (SL)	LF	\$30.90	50	\$1,545.00
601.2615	18" DIA. CPEP (SL)	LF	\$35.80	263	\$9,415.40
601.7010	15" CPEPES	EA	\$371.00	2	\$742.00
601.7015	18" CPEPES	EA	\$357.00	1	\$357.00
604.18	PRECAST REINFORCED CONCRETE CATCH BASIN WITH CAST IRON GATE	EA	\$2,750.00	4	\$11,000.00
616.41	REMOVAL OF EXISTING CURB	LF	\$5.28	320	\$1,689.60
618.10	PORTLAND CEMENT CONCRETE SIDEWALK, 5 INCH	SY	\$60.70	100	\$6,070.00
618.15	BITUMINOUS CONCRETE SIDEWALK	TON	\$215.00	730	\$156,950.00
621.50	MANUFACTURED TERMINAL SECTION, FLARED	EA	\$1,780.00	1	\$1,780.00
621.70	GUARDRAIL APPROACH SECTION, GALVANIZED TYPE I	EA	\$1,940.00	1	\$1,940.00
621.75	REMOVE AND RESET GUARDRAIL	LF	\$5.78	300	\$1,734.00
621.80	REMOVAL AND DISPOSAL OF GUARDRAIL	LF	\$2.02	100	\$202.00
621.81	REMOVAL AND DISPOSAL OF GUIDE POSTS	EA	\$6.99	20	\$139.80
635.11	MOBILIZATION/DEMOBILIZATION	LS	N/A	1	\$16,100.00
641.10	TRAFFIC CONTROL	LS	N/A	1	\$20,000.00
646.20	4" WHITE LINE	LF	\$0.08	1650	\$132.00
646.21	4" YELLOW LINE	LF	\$0.06	620	\$37.20
646.214	6" WHITE LINE	LF	\$0.09	1500	\$135.00
646.215	6" YELLOW LINE	LF	\$0.09	500	\$45.00
646.26	24" STOP BAR	LF	\$1.33	50	\$66.50
646.30	LETTER OR SYMBOL	EA	\$19.90	7	\$139.30
646.31	CROSSWALK MARKING	LF	\$3.53	230	\$811.90
646.85	REMOVAL OF PAVEMENT MARKINGS	SF	\$0.47	1820	\$855.40
656.30	DECIDUOUS TREES	EA	\$244.00	6	\$1,464.00
675.50	REMOVING SIGNS	EA	\$15.10	9	\$135.90
675.60	ERECTING SALVAGED SIGNS	EA	\$24.10	9	\$216.90
677.25	REMOVE AND RESET OVERHEAD TRAFFIC SIGN SUPPORT	EA	\$19,100.00	1	\$19,100.00
900.620	PEDESTRIAN SIGNALS WITH ACTUATION	EA	N/A	2	\$30,000.00

Total within State ROW =	\$540,000
Admin =	\$90,000
25% Detail Design & Construction	\$90,000
25% contingency =	\$90,000
Total =	\$360,000

NOTE: This is a budgetary cost estimate for Kocher Drive Streetscape Improvements Project as noted on the Conceptual Design Plans dated August 14, 2014. This estimate is based on limited available site information. Additional costs could be incurred due to unforeseen issues that would be identified either during the detailed design phase or during construction.

Estimated By: Melissa Wasson Date: 12/12/2013 Revised: August 14, 2014

Checked By: Mark Armbrust, PE Date: 12/12/2013


Kocher Drive Streetscape Improvements Construction Estimate - Town August 2014

ITEM NO.	DESCRIPTION	UNIT	VAOT 5 YR AVG PRICE	ESTIMATED QUANTITY TOWN	TOTAL COST WITHIN TOWN ROW - MATLS	TOTAL COST WITHIN TOWN ROW - LABOR	TOTAL COST WITHIN TOWN ROW - EQUIPMT	TOTAL COST TOWN
201.11	CLEARING AND GRUBBING	ACRE	\$12,400.00	0.05	\$0.00	\$279.00	\$341.00	\$620.00
301.25	SUBBASE OF CRUSHED GRAVEL, COARSE GRADED	CY	\$33.90	85	\$1,613.64	\$864.45	\$403.41	\$2,881.50
618.15	BITUMINOUS CONCRETE SIDEWALK	TON	\$215.00	170	\$23,757.50	\$5,482.50	\$7,310.00	\$36,550.00
656.30	DECIDUOUS TREES	EA	\$244.00	8	\$976.00	\$780.80	\$195.20	\$1,952.00
-								
				Total=	\$26,000.00	\$7,000.00	\$8,000.00	\$42,000
				25% contingency =	\$6,500.00	\$1,750.00	\$2,000.00	\$10,500
				25% Detail Design &	\$6,500.00	\$1,750.00	\$2,000.00	\$10,500
				Construction Admin =	\$6,500.00	\$1,750.00	\$2,000.00	\$10,500
					•	Total w	ithin Town ROW =	\$63,000

NOTE: This is a budgetary cost estimate for Kocher Drive Streetscape Improvements Project as noted on the Conceptual Design Plans dated August 14, 2014. This estimate is based on limited available site information. Additional costs could be incurred due to unforeseen issues that would be identified either during the detailed design phase or during construction.

Estimated By: Melissa Wasson Date: 12/12/2013 Revised: August 14, 2014
Checked By: Mark Armbrust, PE Date: 12/12/2013





Count date 6/19/13

Location Bennington: US7/VT7A/Kocher Drive

Counted by BCRC (Chris Manfredi)

Weather Sunny

Notes 1/2 day of school, no after-school activities

		Koche	er Dr from	East	US	7 from so	uth	VT	7A from W	est	
Start		Right	Thru L	eft	Right	Thru	Left	Right	Thru	Left	Total
9am	Peds	0	1	0	0	0	0	2	1	0	4
	Bikes	0	0	0	0	0	0	1		0	
	Total	0	1	0	0	0	0	3	2	0	6
10	Dl -	0	4		0	0	0		4	0	
10am	Peds Bikes	0	4 0	0 1	0	0	0	0		0	I
	Total	0	4	1	0	0	0	0		<u>0</u>	
	Total	J	7	1	U	U	Ū	"	3	Ū	10
11am	Peds	0	1	0	2	0	0	2	0	0	5
	Bikes	0	0	0	0	0	0	1	0	0	1
	Total	0	1	0	2	0	0	3	0	0	6
12pm	Peds	0	1	0	0	0	1	0		0	I
	Bikes	0	1	0	1	0	0	0		0	
	Total	0	2	0	1	0	1	0	0	0	4
1pm	Peds	0	1	0	1	0	0	4	0	0	6
10111	Bikes	0	0	0	0	0	0	0		0	1
	Total	0	1	0	1	0	0	4		0	
2pm	Peds	0	3	1	1	0	2	0	0	0	7
	Bikes	0	1	0	1	0	1	0		0	
	Total	0	4	1	2	0	3	0	0	0	10
	5 1		4		0	0	4				_
3pm	Peds Bikes	0 0	4 0	0	0	0	1 0	0		0	
	Total	0	4	0 0	0 0	0	<u>0</u>	0 0		0	9
	iotai	U	4	٦	U	U	1	"	4	U	
4pm	Peds	0	0	o	0	0	0	1	4	0	5
'	Bikes	0	1	0	0	0	0	0		0	
	Total	0	1	0	0	0	0	1	4	0	6
	Total	0	18	2	6	0	5	11	15	0	57

Bennington US-7 and Kocher Drive Capacity and Delay Analysis September 4, 2013 Ian Degutis, Traffic Design Vermont Agency of Transportation

Introduction:

In response to a request from the Bennington Regional Planning Commission (BRPC), an analysis of the intersection of US-7 and Kocher Drive in Bennington, VT was performed to assess the traffic impacts associated with the construction of a crosswalk. This signal, MS-106, is part of a 5-signal coordinated corridor which runs east along Kocher Drive and Northside Drive (both VT-7A).

Analysis:

Three concepts were provided to the Agency by the BRPC; Concept 2 was examined in this study, having been selected as the only preferred alternative before the study was requested.

Concept 2 involves the removal of two lanes from the intersection and constructing a sidewalk with crosswalk and pedestrian refuge island. Figure 1, below, is extracted from the conceptual layout provided by the BRPC. The crosswalk would run east-west along the northern edge of Kocher Drive, crossing US-7 at the north side of the intersection. In order to construct the sidewalk the existing dedicated right-turn lane on the eastern leg of Kocher drive would be removed, and the existing through-only lane would become a through-right lane. The refuge island would be constructed in the middle of the north leg of the intersection, US-7, by removing the existing dedicated right-turn lane and shifting the remaining three lanes to the west, with the right-most lane becoming a through-right lane.




Figure 1: Concept 2 in the Area of the Intersection

Traffic counts were performed by the Agency of Transportation's Traffic Research section on May 23, 2013. These counts were taken after the opening of the newly-constructed segment of the Bennington Bypass, and were done on a school-day to account for that traffic as well. Peak hour volumes and factors were included in the report; AM peak hour is from 7:15-8:15, and PM peak hour is from 3:15-4:15. Pedestrian counts were taken by the BRPC on June 19, 2013.

The analysis was performed using Synchro 8 software. Only this intersection was analyzed; current traffic volumes for the entire corridor were not available and a complete corridor analysis is beyond the scope of this study.

Six scenarios were analyzed, each at for AM and PM peak-hour traffic volumes. The scenarios were:

- Existing condition
- Existing geometry with concurrent pedestrian phase
- Dedicated right-turn lane removed from Kocher Drive westbound only, with concurrent pedestrian phase
- Dedicated right-turn lane removed from US-7 southbound only, with concurrent pedestrian phase
- Dedicated right-turn lanes removed from US-7 southbound and Kocher Drive westbound (Concept 2), with concurrent pedestrian phase
- Existing geometry with an exclusive pedestrian phase

For each scenario analyzed, AM and PM peak traffic volumes were examined, using the existing cycle lengths for the signal corridor, 76 seconds for the AM peak, and 90 seconds for the PM peak. Synchro was used to optimize the timings for each scenario at the existing cycle lengths.

Adding the exclusive pedestrian phase requires a longer cycle length to serve all the phases, so a cycle length of 110 seconds was used. It should be noted that this cycle length represents a minimum for this intersection with an exclusive pedestrian phase, and the effect of this cycle length on the rest of the coordinated corridor was not analyzed as part of this study, so these results cannot be directly compared to other results in the table.

The concurrent pedestrian phase was added to Phase 8, the westbound movement on Kocher Drive adjacent to the proposed crosswalk location. For the analysis a Walk time of seven seconds was used, with a Pedestrian Clear time of 25 seconds, both in accordance with guidance in the Manual on Uniform Traffic Control Devices (MUTCD). For the exclusive pedestrian analysis, the same timings were used for the pedestrian phase. An advance pedestrian phase, or delayed green, should be considered. This was not included in this analysis, but would likely have a slight negative impact on delays.

Results of these analyses are shown below, in Table 1.

Table 1: Intersection Delay and Capacity

_		1				
	Cycle Length	Max V/C	Intersection	Intersection	ICU	ICU
	(s)	ratio	Delay (s)	LOS		LOS
Existing Co	ondition					
AM Peak	76	0.75	25.1	С	0.45	Α
PM Peak	90	0.81	28.8	С	0.59	В
Existing G	eometry; Add	Concurrent	Pedestrian Phase			
AM Peak	76	1.28	53.2	D	0.45	Α
PM Peak	PM Peak 90 0.		31.0	С	0.59	В
Remove r	ight turn lane f	rom Koche	r Drive westbound;	Concurrent Pedest	rian Pha	se
AM Peak	76	1.28	53.9	D	0.50	Α
PM Peak	90	0.91	36.9	D	0.70	С
Remove ri	ight turn lane f	rom US-7 s	outhbound; Concurr	ent Pedestrian Pha	ise	
AM Peak	76	1.28	57.6	E	0.47	Α
PM Peak	90	1.01	38.9	D	0.63	В
Remove ri	ight turn lanes	from Koch	er Drive WB and US-	7 SB; Concurrent P	edestria	n Phase
AM Peak	M Peak 76 1.28		58.2	E	0.52	Α
PM Peak			42.9	D	0.73	D

Existing G	eometry; Add E	xclusive Pe	destrian Phase			
AM Peak	110	0.64	34.7	С	0.45	Α
PM Peak	110	1.12	43.0	D	0.59	В

As seen above, adding a concurrent pedestrian phase, even without any geometric changes, doubles the delay at the intersection during the AM peak, and pushes the volume/capacity ratio well above 1.0 for the same time period. The PM peak experiences an increase in delay and higher v/c ratio as well, but the increase is much less. The variation between the results for the two peak hours is caused by the directional splits in traffic volumes. Adding a concurrent pedestrian phase with sufficient time to allow pedestrians to cross the full width of US-7 results in removing green time from the through movements on US-7 and adds it to the through movement on Kocher Drive. The negative effect on intersection is much more pronounced when the predominant traffic movement is on US-7, in the morning.

A complete analysis and potential retiming of the corridor timing would be required as part of the design of any of these alternatives, including comprehensive analysis of delays at all intersections.

The Synchro analysis also determines the Levels of Service for each approach. The results of this analysis, for the same six scenarios, are presented below in Table 2. As above, the values for the exclusive pedestrian phase cannot be directly compared to the other values in the table because the cycle length is increased; the impacts of the longer cycle length were not assessed as part of this study.

Table 2: Level of Service by Approach

	Inter	section	Koche	r Drive	Koche	r Drive	US	S-7	US	5-7
	L	.OS	Easti	bound	West	bound	North	bound	South	bound
			App	roach	Appr	oach	Аррі	oach	Appr	oach
	LOS	Delay	LOS	Delay	LOS	Delay	LOS	Delay	LOS	Delay
Existing Co	ndition									
AM Peak	С	25.1	В	18.2	С	21.8	С	31.8	С	26.8
PM Peak	С	28.8	С	24.2	С	24.6	С	32.1	D	35.9
Existing Ge	ometry	; Add Cor	ncurrent	Pedestria	n Phase					
AM Peak	D	53.2	В	14.6	В	16.0	D	43.0	F	99.1
PM Peak	С	31.0	С	24.9	С	21.1	D	38.9	D	41.2
Remove rig	ght turn	lane fror	m Kocher Drive		stbound ;	Concurre	nt Pedes	trian Pha	se	
AM Peak	D	53.9	В	14.6	В	19.3	D	43.0	F	99.1
PM Peak	D	36.9	C 26.1 C 34.0 D		D	42.3	D	48.1		
Remove rig	ght turn	lane fror	n US-7 s	outhboun	d; Concur	rent Pedes	strian Ph	ase		
AM Peak	Е	57.6	В	14.6	В	16.0	D	50.0	F	106.6
PM Peak	D	38.9	С	25.0	С	21.2	D	38.8	Е	71.2
Remove rig	ght turn	lanes fro	m Koche	er Drive W	/B and US-	7 SB; Con	current F	edestria	n Phase	
AM Peak	Е	58.2	В	14.6	В	19.3	D	50.0	F	106.6
PM Peak	D	42.9	С	26.3	D	36.3	D	41.9	Е	77.2
Existing Ge	ometry	; Add Exc	lusive Pe	edestrian	Phase					
AM Peak	С	34.7	С	28.8	С	29.9	D	44.3	С	35.0
PM Peak	D	43.0	D	52.3	С	34.1	С	31.8	Е	58.3

From these results it is clear that the most-significant increase in delay is on the US-7 southbound approach during the AM peak, and that that increase is caused primarily by the addition of the pedestrian phase, not the removal of the dedicated right turn lane.

Conclusion:

Addition of a crosswalk on the north leg of the intersection of US-7 and Kocher Drive in Bennington will push the intersection's volume/capacity ratio well above 1.0 and more than double delay at certain times of day. Delay on the north approach will nearly quadruple during morning peak-hour traffic flows. The lane removal proposed in Concept 2, as provided by the BRPC, has a slight additional negative impact on traffic, but does not make a significant difference to the intersection delay or capacity.

Recommendation:

If feasible alternatives to the proposed pedestrian crossing at this location exist, they should be pursued first. If no feasible alternative to a crosswalk at this intersection can be identified and a crosswalk is to be constructed at this intersection, VTrans finds no objection to the lane removal as shown in Concept 2.

Proper engineering plans will need to be developed for review by the Agency, and the design consultant should be required to perform a corridor timing optimization analysis of the entire coordinated corridor as a part of the design and plan preparation. The pedestrian phase should be concurrent with the adjacent through movement, but should lead the green. All timings and phasing should be in compliance with the MUTCD, VTrans standards and any other applicable standards or guidance.

Turning Movement Report

File Name: 7-2.33Merged13 Counter: Miovision camera

Counted By: R Gustafson Site Code : 30202770 Weather: Sunny, windy Start Date : 5/23/2013

Page No : 1 Town: 7-2.33 Bennington

Groups Printed- Auto - Medium - Heavy

	US 7 from Shaftsbury From North						om Eas		Rd US 7 from VT 9					VT 7A from VT 67A				
	03 1			ury	KOCII	From		si Ku	,	From		'	VI		West	/ A		
Ct - ut Tius -	1 -44			Dada	1 -44			Dada	1 - 44			Dada	1 -44			Dada	1.4 -	
Start Time	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Int. Total	
Factor	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	107	
06:00 AM	3	9	4	0	1	14	10	0	15	16	4	0	10	14	7	0	107	
06:15 AM	17	12	10	0	2	18	18	0	21	23	2	0	9	17	20	0	169	
06:30 AM	21	17	10	0	7	34	25	0	35	45	7	0	5	35	16	0	257	
06:45 AM	53	29	16	0	12	28	19	0	32	25	14	0	11	39	15	0	293	
Total	94	67	40	0	22	94	72	0	103	109	27	0	35	105	58	0	826	
07:00 AM	35	20	8	0	11	40	11	0	24	31	14	0	9	46	20	0	269	
07:15 AM	65	48	14	0	17	54	19	0	22	28	14	0	13	40	33	0	367	
07:30 AM	79	68	17	0	14	44	20	0	20	39	11	0	13	33	24	0	382	
07:45 AM	30	64	34	0	11	54	22	0	41	41	13	0	17	42	39	0	408	
Total	209	200	73	0	53	192	72	0	107	139	52	0	52	161	116	0	1426	
08:00 AM	19	57	22	0	12	47	13	0	37	29	18	0	10	35	39	0	338	
08:15 AM	25	47	23	0	12	45	15	0	46	32	16	0	13	46	34	0	354	
08:30 AM	16	64	18	0	15	34	11	0	40	25	8	0	14	38	46	0	329	
08:45 AM	22	51	20	0	16	36	8	0	35	39	11	0	8	38	46	0	330	
Total	82	219	83	0	55	162	47	0	158	125	53	0	45	157	165	0	1351	
09:00 AM	17	36	10	0	11	30	10	0	41	34	14	0	13	34	29	0	279	
09:15 AM	21	27	13	0	10	29	16	0	43	28	17	0	12	36	41	0	293	
09:30 AM	8	42	7	0	10	35	14	0	45	30	18	0	7	30	49	0	295	
09:45 AM	14	38	7	0	12	41	18	0	45	43	20	0	14	34	25	0	311	
Total	60	143	37	0	43	135	58	0	174	135	69	0	46	134	144	0	1178	
10:00 AM	14	40	14	0	18	42	15	0	44	28	22	0	15	30	25	0	307	
10:15 AM	19	23	9	0	25	43	17	0	49	31	21	0	10	38	38	0	323	
10:30 AM	17	36	15	0	11	41	22	0	45	32	22	0	6	47	43	0	337	
10:45 AM	22	34	17	0	12	46	8	0	50	28	25	0	15	56	35	0	348	
Total	72	133	55	0	66	172	62	0	188	119	90	0	46	171	141	0	1315	
11:00 AM	12	35	12	0	21	53	17	0	59	29	16	0	14	63	38	0	369	
11:15 AM	20	23	11	0	10	35	21	0	50	23	34	0	16	44	57	0	344	
11:30 AM	20	42	15	0	20	56	18	0	62	30	20	0	14	45	42	0	384	
11:45 AM	10	33	9	0	23	54	19	0	56	36	20	0	15	48	36	0	359	
Total	62	133	47	0	74	198	75	0	227	118	90	0	59	200	173	0	1456	
12:00 PM	14	32	12	0	24	74	29	0	62	55	32	0	16	60	44	0	454	
12:15 PM	15	47	15	0	16	52	24	0	74	46	49	0	12	60	58	0	468	
12:30 PM	14	27	9	0	20	51	24	0	49	36	32	0	12	57	42	0	373	
12:45 PM	20	38	17	0	22	54	21	0	56	31	20	0	13	60	55	0	407	
Total	63	144	53	0	82	231	98	0	241	168	133	0	53	237	199	0	1702	
01:00 PM	24	40	14	0	19	54	24	0	47	34	26	0	16	44	53	0	395	
01:15 PM	15	33	12	0	26	59	12	0	60	36	32	0	13	66	44	0	408	
01:30 PM	21	29	12	ō	34	50	18	0	71	36	18	0	10	67	52	0	418	
01:45 PM	29	32	12	ō	19	47	17	0	62	36	26	0	21	55	43	0	399	
Total	89	134	50	0	98	210	71	0	240	142	102	0	60	232	192	0		
02:00 PM	27	28	13	0	19	53	25	0	69	50	29	0	19	56	46	0	434	
02:15 PM	14	33	12	0	20	75	35	0	64	41	31	0	31	52	47	0	455	
02:30 PM	18	36	13	ő	53	121	50	Ö	64	61	29	Ö	20	68	54	0	587	
02:45 PM	35	44	17	ō	22	68	36	0	63	51	29	0	25	72	52	0	514	
Total	94	141	55	0	114	317	146	0	260	203	118	0	95	248	199	0	1990	
- 1																		

The Vermont Agency of Transportation

Traffic Research/Policy Planning & Intermodal Development Turning Movement Report

Counter: Miovision camera File Name: 7-2.33Merged13

Counted By: R Gustafson Site Code : 30202770 Weather: Sunny, windy Start Date : 5/23/2013

Town: 7-2.33 Bennington Page No : 2

Groups Printed- Auto - Medium - Heavy


	US	7 from S	Shaftsb	ury			om Eas		l	JS 7 fro)	VT	7A fro	m VT 67	7A	
		From		.		From	East			From	South			From	West		
Start Time	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Int. Total
Factor	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	
03:00 PM	23	32	13	0	33	78	57	0	72	54	19	0	30	65	49	0	525
03:15 PM	22	59	16	0	23	75	38	0	61	57	30	0	21	74	52	0	528
03:30 PM	30	44	12	0	21	67	40	0	66	66	15	0	27	78	52	0	518
03:45 PM	25	64	21	0	27	56	37	0	77	45	24	0	20	72	55	0	523
Total	100	199	62	0	104	276	172	0	276	222	88	0	98	289	208	0	2094
04:00 PM	28	47	18	0	23	77	52	0	68	63	27	0	24	67	60	0	554
04:15 PM	28	35	19	0	21	65	45	0	64	55	25	0	26	69	56	0	508
04:30 PM	23	45	16	0	25	61	36	0	69	79	28	0	27	68	42	0	519
04:45 PM	30	48	15	0	18	62	40	0	75	47	15	0	22	81	51	0	504
Total	109	175	68	0	87	265	173	0	276	244	95	0	99	285	209	0	2085
05:00 PM	21	35	13	0	17	69	55	0	76	65	24	0	35	76	37	0	523
05:15 PM	38	51	8	0	16	66	51	0	58	56	22	0	29	78	48	0	521
05:30 PM	14	41	19	0	19	53	28	0	51	51	22	0	25	45	38	0	406
05:45 PM	18	30	17	ő	16	38	24	0	58	33	11	0	16	52	48	0	361
Total	91	157	57	0	68	226	158	0	243	205	79	0	105	251	171	0	1811
	_	_	_	- 1		_			_		_	- 1		_			
Grand Total	1125	1845	680	0	866	2478	1204	0	2493	1929	996	0	793	2470	1975	0	18854
Apprch %	30.8	50.5	18.6	0	19	54.5	26.5	0	46	35.6	18.4	0	15.1	47.2	37.7	0	
Total %	6	9.8	3.6	0	4.6	13.1	6.4	0	13.2	10.2	5.3	0	4.2	13.1	10.5	0	
Auto	1068	1741	656	0	844	2406	1130	0	2409	1844	974	0	763	2382	1923	0	18140
% Auto	94.9	94.4	96.5	0	97.5	97.1	93.9	0	96.6	95.6	97.8	0	96.2	96.4	97.4	0	96.2
Medium	36	55	15	0	15	52	52	0	74	50	19	0	22	75	42	0	507
% Medium	3.2	3	2.2	0	1.7	2.1	4.3	0	3	2.6	1.9	0	2.8	3	2.1	0	2.7
Heavy	21	49	9	0	7	20	22	0	10	35	3	0	8	13	10	0	207
% Heavy	1.9	2.7	1.3	0	8.0	8.0	1.8	0	0.4	1.8	0.3	0	1	0.5	0.5	0	1.1

Turning Movement Report

Counter: Miovision camera File Name: 7-2.33Merged13

Counted By: R Gustafson Site Code : 30202770 Start Date : 5/23/2013 Weather: Sunny, windy

Town: 7-2.33 Bennington Page No : 3




Turning Movement Report

Counter: Miovision camera File Name: 7-2.33Merged13

Counted By: R Gustafson Site Code : 30202770 Weather: Sunny, windy Start Date : 5/23/2013

Town: 7-2.33 Bennington Page No : 4

	U	S 7 fro	om Sh	aftsbu	ıry	Ko	cher I	Or fro	n East	t Rd		US 7	7 from	VT 9		,	VT 7A	from	VT 67	Α	
		Fr	om No	orth			F	rom E	ast			Fr	om Sc	outh			Fr	om W	est		
Start Time	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Int. Total
Peak Hour A	Analysi	s Fron	า 06:00) AM to	11:45	AM - F	Peak 1	of 1													
Peak Hour fo	or Enti	re Inte	rsectio	n Begi	ns at 0	7:15 A	M														
07:15 AM	65	48	14	0	127	17	54	19	0	90	22	28	14	0	64	13	40	33	0	86	367
07:30 AM	79	68	17	0	164	14	44	20	0	78	20	39	11	0	70	13	33	24	0	70	382
07:45 AM	30	64	34	0	128	11	54	22	0	87	41	41	13	0	95	17	42	39	0	98	408
08:00 AM	19	57	22	0	98	12	47	13	0	72	37	29	18	0	84	10	35	39	0	84	338
Total Volume	193	237	87	0	517	54	199	74	0	327	120	137	56	0	313	53	150	135	0	338	1495
% App. Total	37.3	45.8	16.8	0		16.5	60.9	22.6	0		38.3	43.8	17.9	0		15.7	44.4	39.9	0		
PHF	.611	.871	.640	.000	.788	.794	.921	.841	.000	.908	.732	.835	.778	.000	.824	.779	.893	.865	.000	.862	.916
Auto	188	222	85	0	495	52	188	65	0	305	107	124	54	0	285	51	143	128	0	322	1407
% Auto	97.4	93.7	97.7	0	95.7	96.3	94.5	87.8	0	93.3	89.2	90.5	96.4	0	91.1	96.2	95.3	94.8	0	95.3	94.1
Medium	4	9	2	0	15	1	6	8	0	15	7	10	2	0	19	2	6	5	0	13	62
% Medium								10.8	0	4.6	5.8	7.3	3.6	0	6.1	3.8	4.0	3.7	0	3.8	4.1
Heavy	1	6	0	0	7	1	5	1	0	7	6	3	0	0	9	0	1	2	0	3	26
% Heavy	0.5	2.5	0	0	1.4	1.9	2.5	1.4	0	2.1	5.0	2.2	0	0	2.9	0	0.7	1.5	0	0.9	1.7



Turning Movement Report

Counter: Miovision camera File Name: 7-2.33Merged13

Counted By: R Gustafson Site Code : 30202770 Start Date : 5/23/2013 Weather: Sunny, windy

Town: 7-2.33 Bennington Page No : 5

	U	S 7 fro	om Sh	aftsb	ury	Ko	cher I	Dr froi	m Eas	t Rd		US	7 from	VT 9		,	VT 7A	from	VT 67	Ά	
		Fr	om No	orth			F	rom E	ast			Fr	om So	outh			Fi	om W	/est		
Start Time	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Int. Total
Peak Hour A	,							of 1													
Peak Hour fo	or Enti	re Inte	rsectio	n Beg	ins at 0	3:15 P	M														
03:15 PM	22	59	16	0	97	23	75	38	0	136	61	57	30	0	148	21	74	52	0	147	528
03:30 PM	30	44	12	0	86	21	67	40	0	128	66	66	15	0	147	27	78	52	0	157	518
03:45 PM	25	64	21	0	110	27	56	37	0	120	77	45	24	0	146	20	72	55	0	147	523
04:00 PM	28	47	18	0	93	23	77	52	0	152	68	63	27	0	158	24	67	60	0	151	554
Total Volume	105	214	67	0	386	94	275	167	0	536	272	231	96	0	599	92	291	219	0	602	2123
% App. Total	27.2	55.4	17.4	0		17.5	51.3	31.2	0		45.4	38.6	16	0		15.3	48.3	36.4	0		
PHF	.875	.836	.798	.000	.877	.870	.893	.803	.000	.882	.883	.875	.800	.000	.948	.852	.933	.913	.000	.959	.958
Auto	102	211	65	0	378	92	267	159	0	518	265	226	94	0	585	90	283	217	0	590	2071
% Auto	97.1	98.6	97.0	0	97.9	97.9	97.1	95.2	0	96.6	97.4	97.8	97.9	0	97.7	97.8	97.3	99.1	0	98.0	97.6
Medium % Medium	0	2	1	0	3	1	6	4	0	11	7	3	2	0	12	2	5	1	0	8	34
Heavy	3	1	1	0	5	1	2	4	0	7	0	2	0	0	2	0	3	1	0	4	18
% Heavy	2.9	0.5	1.5	0	1.3	1.1	0.7	2.4	0	1.3	0	0.9	0	0	0.3	0	1.0	0.5	0	0.7	0.8

